



MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.
**EASY TEXTURE CEILING ACOUSTIC
 ITEM #4095**

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH,
 4=EXTREME) (I=SAFETY GLASSES, GLOVES, VAPOR RESPIRATOR)

| HAZARDOUS MATERIAL INFORMATION SYSTEM | |
|---------------------------------------|---|
| HEALTH | 1 |
| FLAMMABILITY | 3 |
| REACTIVITY | 0 |
| PROTECTIVE EQUIPMENT | J |

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:
 HOMAX PRODUCTS, INC.
 468 West Horton Road
 BELLINGHAM WA 98226

24 HOUR EMERGENCY PHONE NUMBER:

CHEMTREC 1-800-424-9300

INFORMATION PHONE NUMBER: 1-800-729-9029

DATE OF PREPARATION: 05/15/03

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

| CAS NUMBER | DESCRIPTION | PEL | TLV | % | LD50 |
|------------|-------------------------|-----|-------|---------|--------------------------------------|
| 107-41-5 | HEXYLENE GLYCOL | N/A | 25PPM | | |
| 115-10-6 | DIMETHYL ETHER PROPELLA | N/A | N/A | 500 PPM | 164000 PPM/4H R RAT INHA |

*** NO TOXIC CHEMICAL (S) SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III AND OF 40 CFR 372 ARE PRESENT.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

| | |
|--------------------------------|---|
| APPEARANCE AND ODOR: | WHITE/SLIGHT ETHEREAL ODOR |
| BOILING POINT: | - 13 DEG F. |
| FREEZING POINT: | 32F PH: N/A |
| WATER SOLUBILITY %: | SOLUBILE IN WATER |
| VAPOR DENSITY (AIR = 1): | HEAVIER THAN AIR |
| EVAPORATION RATE: | FASTER THAN N-BUTYL ACETATE |
| SPECIFIC GRAVITY (WATER = 1) | 1.1 |
| MATERIAL V.O.C. | 1.01 LBS/IMP GAL .84 LBS/US GAL 101 GMS/LTR |
| COEFFICIENT OF WATER/OIL DIST. | N/A |
| ODOR THRESHOLD: | N/A |

N/E = NOT ESTABLISHED

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): <0DEG F METHOD USED: TOC

UNIFORM FIRE CODE STANDARD 88-1 LEVEL ONE AEROSOL

FLAMMABLE LIMITS IN AIR BY VOLUME LOWER: 1.3%
UPPER: 18.0 %

EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG

SPECIAL FIREFIGHTING PROCEDURES:

KEEP CONTAINER COOL WITH WATER SPRAY OR FOG, UNTIL FIRE HAS BEEN EXTINGUISHED.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

CLOSED CONTAINERS MAY EXPLODE DUE TO BUILD UP OF PRESSURE FROM EXTREME HEAT OR FIRE.

FLAMMABILITY:

T.D.G.R. CLASS

SENSITIVITY TO IMPACT:

DO NOT PUNCTURE

SENSITIVITY TO STATIC DISCHARGE:

PRIMARILY VAPORS

SECTION V - REACTIVITY DATA

STABILITY:

MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

INCOMPATIBILITY (MATERIALS TO AVOID):

STRONG OXIDIZING AGENTS

HAZARDOUS DECOMPOSITION PRODUCTS:

IF HEATED WITH PEROXIDES PRESENT, VIOLENT DECOMPOSITION CAN OCCUR.

CONDITIONS TO AVOID:

HIGH TEMPERATURES.

SECTION VI - HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION: YES SKIN: YES

HEALTH HAZARDS (ACUTE AND CHRONIC):

INHALATION: ANESTHETIC. IRRITATION OF THE RESPIRATORY TRACT, OR NERVOUS SYSTEM DEPRESSION- CHARACTERIZED BY HEADACHE, DIZZINESS, NAUSEA, OR POSSIBLE UNCONSCIOUSNESS.
SKIN OR EYE CONTACT: PRIMARY IRRITATION. PROLONGED OR REPEATED CONTACT TO SKIN MAY CAUSE DERMITITIS-EXERCISE DUE CARE.

INHALATION:

MAY CAUSE DIZZINESS OR NAUSEA.

SKIN ASORBTION:

MAY CAUSE IRRITATION OR BURNING SENSATION.

SKIN AND EYE CONTACT:

MAY CAUSE IRRITATION OR BURNING SENSATION.

INGESTION:

N/A

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

THIS PRODUCT DOES NOT CONTAIN ANY RECOGNIZED CARCINOGEN.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

NONE KNOWN.

EMERGENCY AND FIRST AID PROCEDURES:

VAPORS: REMOVE FROM EXPOSURE AND RESTORE BREATHING, SEEK MEDICAL ATTENTION.

SPLASH: (SKIN) WASH AFFECTED AREA, REMOVE CONTAMINATED CLOTHING, SEE PHYSICIAN IF ANY IRRITATION PERSISTS.

SPLASH: (EYES) FLUSH IMMEDIATELY WITH WATER FOR 15 MINUTES AND TAKE TO PHYSICIAN.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

REMOVE ALL SOURCES OF IGNITION: FLAMES, SPARKS, STATIC ELECTRICITY & ELECTRICAL.

VENTILATE AREA AND SOAK UP WITH INERT ABSORBENT USING NON-SPARKING TYPE TOOLS..

WASTE DISPOSAL:

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

DO NOT STORE ABOVE 120DEG F. DO NOT STORE OR USE NEAR HEAT, SPARKS, OR FLAME.

OTHER PRECAUTIONS:

DO NOT GET IN EYES. DO NOT BREATHE VAPORS. AVOID SKIN CONTACT. DO NOT TAKE INTERNALLY.

SMOKING WHILE USING THIS PRODUCT MUST BE STRICTLY PROHIBITED. IN ADDITION TO ALL OTHER HAZARDS AND PRECAUTIONS-DUST FROM SANDING THE DRY PAINT FILMS SHOULD BE TREATED AS A NUISANCE DUST WITH A TLV OF 10MG/CUBIC METER.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION:

OUTDOORS: APPROVED MECHANICAL PARTICULATE FILTER TO REMOVE AIRBORNE OVERSPRAY IN RESTRICTED AREAS WITH POOR VENTILATION USE NIOSH APPROVED ORGANIC CARTRIDGE RESPIRATOR.

VENTILATION:

ALL APPLICATION AREAS SHOULD BE ADEQUATELY VENTILATED IN ORDER TO KEEP THE INGREDIENTS IN SECTION II BELOW THEIR EXPOSURE LIMITS.

PROTECTIVE GLOVES:

IMPERVIOUS GLOVES ARE RECOMMENDED TO PREVENT SKIN CONTACT.

EYE PROTECTION:

SAFETY GLASSES WITH SIDE SHIELDS ARE RECOMMENDED TO PREVENT EYE CONTACT.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT:

EYES-WASH FOUNTAIN AND SAFETY SHOWER.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE.

WORK/HYGIENIC PRACTICES:

AVOID PROLONGED OR REPEATED CONTACT. DO NOT BEATHE VAPORS.

SECTION IX - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX PROUDCTS, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HEREWITH.

PROPER SHIPPING NAME: CONSUMER COMMODITY

HAZARD CLASS NUMBER : ORM-D