

# Material Safety Data Sheet

## MANUFACTURER:

**GPM**  
**201 Jandus Road**  
**Cary, IL 60013**

EMERGENCY TELEPHONE NUMBER:  
(800)228-5635 ext 017  
DATE: November 03, 2003

TECHNICAL INFORMATION:  
(800)345-9218  
SUPERSEDES: October 24, 2003

HMIS:  
H [1]  
F [0]  
R [0]

## SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT CODE: DL - 1, 2, 3, 4, 5, 10, 13, 15, D, N, T  
PRODUCT NAME: Premium Latex Floor & Porch  
PRODUCT CLASS: Interior/Exterior Nonflat Latex Paint

## SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENT	CAS NUMBER	WT. %	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE mmHg@20°C
			TLV	PEL	
(S)2-Butoxyethanol	111-76-2	1 - 3	25ppm	25ppm	0.88
Carbon Black(1)	1333-86-4	.1 - 3	3.5mg/m <sup>3</sup>	3.5mg/m <sup>3</sup>	17.0
Crystalline Silica	14808-60-7	2 - 6	0.1mg/m <sup>3</sup>	0.1mg/m <sup>3</sup>	NA
Propylene Glycol	57-55-6	3 - 5	400ppm	400ppm	0.1
Red Iron Oxide (2)	1309-37-1	2 - 8	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>	NA
Yellow Iron Oxide (3)	51274-00-1	2 - 4	5mg/m <sup>3</sup>	5mg/m <sup>3</sup>	NA

(S) - This ingredient is subject to the reporting requirements of Section 313 SARA Title III.

(1) - DL-2, 3, 5, 10, & 13 only. (2) - DL-4, 13 only. (3) - DL-13, 15 only.

NA - Not applicable. NE - Not established.

## SECTION 3 - PHYSICAL DATA

VAPOR DENSITY:  HEAVIER  LIGHTER THAN AIR BOILING RANGE: 210-220°F  
EVAPORATION RATE:  FASTER  SLOWER THAN ETHER 68 -74% VOLATILE VOLUME  
APPEARANCE/ODOR: Thick liquid/slight ammonia DENSITY: 8.7 -10.1 Wt(lbs)/Gal  
VOLATILE ORGANIC COMPOUND(VOC): Less than 250 gm/l 2.10 lbs/gal

## SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION OSHA N/A FLASH POINT N/A LEL N/A  
DOT Not Regulated

EXTINGUISHING MEDIA:

FOAM  ALCOHOL FOAM  CO<sub>2</sub>  DRY CHEMICAL  WATER FOG  OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat.

SPECIAL FIRE FIGHTING PROCEDURES: Use a self-contained breathing apparatus with full face mask in a positive pressure demand mode. Water may be used to cool containers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide.

### **SECTION 5 - HEALTH HAZARD DATA**

#### EFFECTS OF OVEREXPOSURE:

**INHALATION:** Vapors or spray mists may be irritating to eyes, nose or throat. Prolonged overexposure may cause coughing, shortness of breath, dizziness, and intoxication. This product contains crystalline silica (cs), which is considered a hazard by inhalation.

**SKIN CONTACT:** Prolonged or repeated contact may cause irritation.

**EYE CONTACT:** Direct eye contact will result in mild irritation.

**INGESTION:** Ingestion of large quantities may result in nausea or other gastrointestinal irritation.

**CARCINOGENICITY:** This product contains carbon black (See Section 2). Carbon black is classified by IARC (but not by NTP or OSHA) as a possible carcinogen for humans (2B) based on laboratory animal studies.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:** None known to GPM

**PRIMARY ROUTE(S) OF ENTRY:** [X] DERMAL [X] INHALATION [ ] INGESTION

#### EMERGENCY AND FIRST AID PROCEDURES:

**INHALATION:** Remove to fresh air.

**SKIN CONTACT:** Remove contaminated clothing. Wash affected area. Launder clothes before reuse.

**EYE CONTACT:** Flush immediately with large amounts of water. Contact physician if irritation persists.

**INGESTION:** Give 1 or 2 glasses of water to dilute. Do not induce vomiting. Call physician immediately.

---

### **SECTION 6 - REACTIVITY DATA**

**STABILITY:** Stable                      **HAZARDOUS POLYMERIZATION:** Will not occur

**INCOMPATIBILITY (Materials to avoid):** None known

---

### **SECTION 7 - SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Contain spill. Absorb liquid with clay, sand or floor absorbent. Prevent run-off to sewers, streams or other bodies of water.

**WASTE DISPOSAL METHOD:** Observe all federal, state and local regulations regarding proper disposal.

---

### **SECTION 8 - SAFE HANDLING AND USE INFORMATION**

**RESPIRATORY PROTECTION:** None required when brushed or rolled if good ventilation is maintained. During spray application, an approved mechanical filter respirator should be used to remove airborne particles of overspray.

**VENTILATION:** Sufficient ventilation should be provided to keep air contaminant concentration below applicable OSHA or ACGIH limits.

**PROTECTIVE CLOTHING:** Safety glasses with splash guards to prevent contact.

**OTHER PROTECTIVE EQUIPMENT:** Eyewash facility and safety shower in the event of a spill.

**HYGIENIC PRACTICES:** Wash hands before eating, drinking or smoking.

---

### **SECTION 9 - SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Store in a cool dry area. Close container after each use.

**OTHER PRECAUTIONS:** Keep out of reach of children. Keep from freezing. Avoid prolonged skin contact. Do not take internally.

**WARNING:** This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

---

The information contained in this MSDS is based on information and data provided by the supplier of the raw material used in the manufacture of this product. Although GPM believes such information and data to be reliable, GPM makes no warranty, expressed or implied, regarding the accuracy and completeness of such information and data.