
MATERIAL SAFETY DATA SHEET

Product Name: SCOTT'S LIQUID GOLD WOOD CLEANER &PRESERVATIVE (AEROSOL)

HMIS Rating: Health (1) Flammability (3) Reactivity (0)

HMIS Scale: 4=Very High 3=High 2=Moderate 1=Slight 0=Insignificant

Section I - Hazardous Ingredients

<u>Chemical Name</u>	<u>CAS Number</u>	<u>OSHA(PEL)</u>	<u>ACGIH(TLV)</u>
Petroleum Process Oil (oil mist in air)	64742-56-9	5mg/m3	5mg/m3
VM&P Naphtha	64742-89-8	300 ppm	300 ppm
Carbon Dioxide	124-38-9	10,000 ppm	10,000 ppm

Section II - Physical Data (Liquid Phase)

Appearance and Odor: Amber liquid with almond or lemon odor

Boiling Point - 170° F

Evap. Rate (BuAc=1) -n/e

Specific Gravity - 0.844 gm/cc

Vapor Density - >1.0

Solubility in Water - None

% Volatile - n/e

pH - n/a

Vapor Pressure - n/e

Section III - Fire & Explosion Hazard

Flash Point/Method - 112° F - TCC (Liquid) Aerosol - Flammable LEL - n/e UEL - n/e

Unusual Fire/Explosion Hazard: Vapors may be heavier than air, may travel and flash back. Containers may burst at temperatures above 130 F.

Special Fire Fighting Procedures: Use self contained breathing apparatus, avoid breathing fumes. Cool containers in water fog.

Extinguishing Media - Water spray, foam, CO2, dry chemical.

Section IV - Reactivity Data

Stability: Stable

Incompatibility: Strong oxidizers, acids, and alkalis.

Hazardous Polymerization: Will () Will not (X) occur

Conditions to avoid: Heat, open flames, and aluminum

Hazardous Decomposition / By-Products: Combustion will release Carbon Monoxide and/or Carbon Dioxide, and other unidentified organic compounds.

Section V - Health Hazard/First Aid Information

Chronic Health Hazard - None

TLV - n/a

Carcinogenicity - NTP ()

IARC ()

OSHA ()

Prop.65 ()

None (X)

	Route	Effects of Overexposure	First Aid Procedures
Eyes	X	Stinging or redness	Flush with water for 15 minutes.
Ingestion	X	Digestive discomfort	Do not induce vomiting as aspiration pneumonitis may result.
Skin	X	Redness or irritation	Rinse thoroughly with soap and warm water.
Inhalation	X	Prolonged exposure may cause nausea, dizziness, headache. Massive overexposure may cause unconsciousness, death.	Remove to fresh air.

SEEK MEDICAL ATTENTION IF ABOVE SYMPTOMS PERSIST.

Section VI - Spill or Leak Procedures

Spillage/Release - Eliminate sources of ignition, avoid breathing vapors, minimize skin contact. Recover liquid with absorbent material and dispos. Ventilate spill area.

Waste Disposal - Follow Local, State, and Federal Regulations.

Section VII - Special Protection/Handling Information

- Ventilation - Adequate to minimize vapor.
- Respiratory Protection - Use breathing apparatus in enclosed areas.
- Gloves - Protective gloves during prolonged contact.
- Eye Wear - Safety glasses, do not wear contact lenses.

Precautions in Handling & Storage - Keep containers closed when not in use. Avoid unnecessary contact with fumes or liquid. Do not store near heat, sparks, open flames, or strong oxidizers.

Section VIII - Additional Information

n/a =not applicable n/e =not established