

**MATERIAL SAFETY DATA SHEET**

Manufacturer's Name:

**Masterchem®Industries, Inc.**

3135 Old Highway M

Imperial, MO 63052

Company Code: MTER

Issue Date: October 10, 2001

Transportation

Emergencies:

Call Chemtrec

1-800-424-9300

Emergency Telephone No.

1-800-325-3552

Medical Emergencies:

1-866-303-6951

NPCA HAZARDOUS MATERIALS IDENTIFICATION SYSTEM		
RATING	IDENTIFICATION	
4 = EXTREME	HEALTH	3
3 = HIGH	FLAMMABILITY	4
2 = MODERATE	REACTIVITY	0
1 = SLIGHT	CHRONIC HEALTH	See Section V
0 = MINIMAL		

**Section I - Product Identification**

PRODUCT NAME: **Kilz® Aerosol**  
 PRODUCT NUMBER: 51652-10004-4  
 PRODUCT CLASS: Aerosol Spray Primer (60% VOC)

**SECTION II A-HAZARDOUS INGREDIENTS**

CAS REGISTRY NO.	%W	CHEMICAL NAME(S)	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE	LISTED AS A CARCINOGEN
			TLV	PEL		
64742-89-8	17.60	VM & P Naphtha (Aliphatic Hydrocarbon)	300 ppm	300 ppm	15 mm @ 37.7°C	No
68476-86-8	24.00	Propellant (Propane/Butane/Isobutane Blend)	900 ppm	900 ppm	70 PSIG @ 25°C	No
67-64-1	15.50	Acetone	750 ppm	750 ppm	231 mm HG @ 25°C	No
108-03-2	2.40	1-Nitropropane	25 ppm	25 ppm	7.5mm HG @ 20°C	No

**SECTION II B – OTHER INGREDIENTS**

71243-64-6	5-15	Alkyd Resin	-	-	-	No
13463-67-7	10-25	Titanium Dioxide	-	-	-	No

**SECTION III - PHYSICAL DATA**

APPEARANCE: White, Aerosol Spray	ODOR: Mild, Sweet Ketone
BOILING RANGE: Minus 43.7° F to plus 282° F	VAPOR DENSITY: <input checked="" type="checkbox"/> HEAVIER <input type="checkbox"/> LIGHTER THAN AIR
EVAPORATION RATE: <input checked="" type="checkbox"/> FASTER <input type="checkbox"/> SLOWER THAN BUTYL ACETATE	<u>82.27%</u> VOLATILE VOLUME: 7.59 POUNDS WT/GAL

**SECTION IV - FIRE AND EXPLOSION HAZARD DATA**

FLAMMABILITY CLASSIFICATION: OSHA 1A	FLASH POINT: Minus 156° F FTCC	LEL: 1.8	DOT: Consumer Commodity ORM-D
--------------------------------------	--------------------------------	----------	-------------------------------

**EXTINGUISHING MEDIA:**

DRY CHEMICAL <input checked="" type="checkbox"/>	ALCOHOL FOAM <input type="checkbox"/>	WATER FOG <input type="checkbox"/>	FOAM <input checked="" type="checkbox"/>	CO <sub>2</sub> <input checked="" type="checkbox"/>	OTHER
--	---------------------------------------	------------------------------------	--	---	-------

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Explosive air/vapor mixtures may form when exposed to heat. Vapors are heavier than air and may travel along the ground and be ignited by open flame, sparks, static discharge or by other sources of ignition. Containers may burst when exposed to extreme heat. Over exposure to combustion products may cause a health hazard. Obtain medical attention.

**SPECIAL FIREFIGHTING PROCEDURES:** Full protective equipment, including self-contained breathing apparatus, should be used to protect firefighters from any hazardous combustion products.

**SECTION V - HEALTH HAZARD DATA**

**EFFECTS OF OVEREXPOSURE:** Inhalation: Anesthetic, irritation of the respiratory tract or acute nervous system depression characterized by the following progressive steps; headache, dizziness, staggering gait, confusion, unconsciousness, or coma. Skin or eye contact: Primary irritant.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:** Reports have associated repeated and prolonged occupation overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**PRIMARY ROUTE(S) OF ENTRY:**

DERMAL <input checked="" type="checkbox"/>	INHALATION <input checked="" type="checkbox"/>	INGESTION <input checked="" type="checkbox"/>
--	--	---

**EMERGENCY AND FIRST AID PROCEDURES:** Inhalation: Remove to fresh air. If respiration has stopped restore breathing. Treat symptomatically. Consult a physician. Splash (eyes): Flush immediately with large amounts of water for at least 15 minutes. Take to physician for medical treatment. Splash (skin): Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. Ingestion: Drink 1 or 2 glasses of water to dilute. Do **not** induce vomiting. Consult physician or poison control center immediately. Treat symptomatically.

**SECTION VI - REACTIVITY DATA**

**STABILITY:** UNSTABLE  STABLE   
**HAZARDOUS POLYMERIZATION:** MAY OCCUR  WILL NOT OCCUR

**HAZARDOUS DECOMPOSITION PRODUCTS:** May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: carbon monoxide, carbon dioxide, hydrocarbons, oxides of nitrogen and other products of combustion.

**CONDITIONS TO AVOID:** High temperatures or high humidities. Heat, sparks or open flame.

**INCOMPATIBILITY: (MATERIALS TO AVOID)** Peroxides or strong oxidizing agents.

**SECTION VII - SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Limit spread of spill or leak. Remove all sources of ignition and ventilate area. Soak up with inert absorbent material. Use non-sparking tools when removing wet absorbent. See Section VIII for required protective measures. Keep material out of sewers and/or drains.

**WASTE DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations. Dry primer and empty aerosol containers may be landfilled. Full or partially full aerosol containers should not be punctured or incinerated and should be treated as hazardous waste which requires disposal at an approved hazardous waste site.

**SECTION VIII-SAFE HANDLING AND USE INFORMATION**

**RESPIRATORY PROTECTION:** If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or Equivalent) or leave the area.

**VENTILATION:** Open doors and windows to provide ventilation of sufficient volume and pattern to keep air contaminant concentrations below occupational exposure limits as shown in Section II A.

**PROTECTIVE GLOVES:** Required, rubber or neoprene to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including splash guards or side shields.

**OTHER PROTECTIVE EQUIPMENT:** Wear protective clothing. Remove and wash contaminated clothing before re-use.

**HYGIENIC PRACTICES:** Wash hands before eating or using the washroom. Smoke in smoking areas only.

**SECTION IX - SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Store away from extreme heat, fire, or open flame. Store in accordance with OSHA 1910.106. Store in well ventilated areas. Store as level 3 aerosol (NFPA 30B).

**OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY.** Avoid breathing vapors and spray mists. Avoid contact with skin and eyes. Protect containers from damage. Do not heat, puncture or incinerate containers. Contents under pressure and may contain explosive vapors. Do not remove or deface label. Keep out of the reach of children.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The product is no more hazardous than its component parts pursuant to 29CFR 1910.1200 (D). The technical information on this MSDS sheet is based upon information submitted by manufacturers and additional information furnished by distributor's chemical suppliers and manufacturers. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in his use of the material.

PREPARED BY: William R. Benton  
Updated by: Mark J. Cyganiak

DATE PREPARED: April 7, 2003  
Updated: May 3, 2004

TITLE: MSDS Coordinator

SUPERSEDES: April 28, 1999

Kilz Aero

(Signature Available upon Request)