

# **MATERIAL SAFETY DATA SHEET**

**PRODUCT TRADE NAME:** 

HOMAX PRODUCTS, INC.

KNOCKDOWN TEXTURE
ITEM #8323

(HAZARD RATING: 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME, \*=CHRONIC) (A=SAFETY GLASSES)

HAZARDOUS MATERIAL INFORMATION SYSTEM	
HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PROTECTIVE EQUIPMENT	A

#### **SECTION I - MANUFACTURER IDENTIFICATION**

MANUFACTURER'S NAME: HOMAX PRODUCTS, INC. 468 WEST HORTON ROAD BELLINGHAM WA 98226 24 HOUR EMERGENCY PHONE NUMBER:

CHEMTREC 1-800-424-9300

INFORMATION PHONE NUMBER: 1-800

1-800-729-9029

DATE OF PREPARATION: 01/15/03

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION							
CAS		WEIGHT		VAPOR PRESS.	LEL		
NUMBER	DESCRIPTION	PERCENT	SARA	(mm HG TEMP @ 20 C)	(@25 C)		
14807-96-6	TALC	5-10	NO	N/A	N/A		
01318-00-9	HEXYLENE GLYCOL	1-5	NO	0.05	N/A		

THE DRIED FILM OF THIS PRODUCT MAY BECOME A DUST NUISANCE WHEN REMOVED BY SANDING OR GRINGING. OSHA RECOMMENDS A PEL/TWA OF 15 mg/m3 FOR TOTAL DUST AND 5mg/m3 FOR THE RESPIRABLE FRACTION. ACGIH RECOMMENDS A TLV/TWA OF 10mg/m3 FOR TOTAL DUST.

SKIN ABSORPTION MAY CONTRIBUTE TO THE OVERALL EXPOSURE TO THIS MATERIAL. TAKE APPROPRIATE MEASURES TO PREVENT SKIN CONTACT.

(N/E – NOT EXTABLISHED)

# SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/E

VAPOR DENSITY: >1 (AIR = 1) EVAPORATION RATE: <1 (ETHER = 1)

% VOLATILE BY VOLUME: 59.56 (THEORÉTICAL) % VOLATILE BY WEIGHT: 36.84 (THEORETICAL) KILOGRAMS PER LITER: 1.612 (THEORETICAL)

N/E - NOT ESTABLISHED

# **SECTION IV - FIRE AND EXPLOSION DATA**

OSHA FLAMMABILITY CLASS:

FLASH POINT: +/- DEGREES F (SETAFLASH)

EXTINGUISHING MEDIA: N/A SPECIAL FIRE FIGHTING N/A

PROCEDURES:

UNUSUAL FIRE AND EXPLOSION NO HAZARD

HAZARDS:

### **SECTION V - REACTIVITY DATA**

STABILITY:

**STABLE** 

HAZARDOUS POLYMERIZATION:

WILL NOT OCCUR

CONDITIONS AND MATERIALS TO AVOID:

NONE RECOGNIZED

HAZARDOUS DECOMPOSITION PRODUCTS:

CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

#### **SECTION VI – HEALTH HAZARD DATA**

EYE CONTACT:

ANY FOREIGN MATERIAL ENTERING INTO THE EYE MAY CAUSE IRRITATION.

SKIN CONTACT:

EXPOSURE MAY PRODUCE SKIN IRRITATION.

INHALATION:

EXPOSURE MAY PRODUCE IRRITATION TO THE NOSE, THROAT, RESPIRATORY TRACT, AND OTHER MUCOUS MEMBRANES.

INGESTION:

THIS PRODUCT MAY BE IRRITATING TO THE GASTROINTESTINAL TRACT IF INGESTED.

#### SIGNS AND SYMPTOMS OF EXPOSURE:

SYMPTOMS OF EYE IRRITATION INCLUDE PAIN, TEARING, REDDENING AND SWELLING. SYMPTOMS OF SKIN IRRITATION INCLUDE REDDENING, SWELLING, RASH AND REDNESS. SYMPTOMS OF RESPIRATORY IRRITATION INCLUDE RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH, AND REDUCED LUNG FUNCTION. SYMPTOMS OF GASTROINTESTINAL IRRITATION INCLUDE SORE THORAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

# MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

PREEXISTING EYE, SKIN, OR RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

WARNING:

THIS PRODUCT CONTAINS A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

#### OTHER HEALTH EFFECTS:

BASED ON THE PRESENCE OF COMPONENT 1 CHRONIC OVEREXPOSURE TO TALC DUST MAY CAUSE SCARRING OF THE LUNGS.

# SECTION VII - EVERGENCY AND FIRST AID PROCEDURES

# **EYE CONTACT:**

IMMEDIATELY FLUSH EYES WITH LOTS OF RUNNING WATER FOR 15 MINUTES, GET IMMEDIATE MEDICAL ATTENTION IF SYMPTOMS PERSIST.

#### SKIN CONTACT:

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

### INHALATION:

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

### **INGESTION:**

DILUTE WITH LIGUID UNLESS THE VICTIM IS UNCONSCIOUS OR VERY DROWSY. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS. CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO AN EMERGENCY FACILITY IMMEDIATELY.

#### **SECTION VIII - PERSONAL PROTECTION**

### RESPIRATORY PROTECTION:

USE VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATIONS – AT LEAST 10 AIR CHANGES PER HOUR AREA RECOMMENDED FOR GOOD GENERAL ROOM VENTILATION. IF EXPOSURE EXCEEDS THE PEL/TLV, USE THE APPROPRIATE NIOSH-APPROVED RESPIRATOR.

### PROTECTIVE CLOTHING:

WEAR SAFETY GLASSES. GOGGLES, OR A SPLASH SHIELD TO PREVENT EYE CONTACT. CONTACT LENSES SHOULD NOT BE WORN. WEAR NEOPRENE OR OTHER SOLVENT RESISTANT GLOVES TO PREVENT SKIN CONTACT.

# ADDITIONAL PROTECTIVE MEASURES:

EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY ROOM.

# **SECTION IX - ENVIRONMENTAL PROTECTION**

# SPILL OR LEAK PROCEDURES:

LARGE SPILLS: EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING, SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS. CONTAIN RUN – OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL. PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE. DISPOSE OF FLUSH SOLUTIONS AS ABOVE.

SMALL SPILLS: TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTYLY FOR PROPER DISPOSAL.

#### WASTE DISPOSAL:

OBSERVE ALL FEDERAL, PROVINCIAL, AND LOCAL REGULATIONS REGARDING PROPER DISPOSAL OF WASTE MATERIAL.

#### **SECTION X – SPECIAL PRECAUTIONS**

KEEP LIQUID AND VAPOR AWAY FROM HEAT, SPARKS, AND FLAME. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER POSSIBLE SOURCE OF IGNITION PRIOR TO USE AND UNTIL VAPORS ARE GONE. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE PRODUCT IN THE ABSENCE OF SPARKS OR FLAME, VAPORS MAY ACCUMULATE AND TRAVEL TO IGITION SOURCES DISTANT FROM HANDLING SITE. KEEP CONTAINER CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION, CONTAINERS, EVEN IF EMPTY, CAN CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, DRILL, GRIND, OR WELD NEAR CONTAINERS.

# **SECTION XI - DISCLAIMER**

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED FROM SOURCES CONSIDERED TO BE RELIABLE. TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ALL INFORMATION IS ACCURATE AND IS PROVIDED IN GOOD FAITH. HOWEVER, NO GUARANTEE OF ACCURACY IS MADE OR IMPLIED.