



Barnes Distribution

1300 E. 9th Street, #700
Cleveland OH 44114
(800) 726-9626



Material Safety Data Sheet

MSDS Form No. : 75919
Item No. : 24805, 24805-1

**** MATERIAL SAFETY DATA SHEET ****

GLOSS WHITE PAINT - HIGH SOLIDS

Part # 75919

**** SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION ****

MSDS Name: GLOSS WHITE PAINT - HIGH SOLIDS
Product CAS: (none)
Product Code:
Synonyms: 24805; 24805-1; GLOSS WHITE PAINT - HIGH SOLIDS
Company Identification:
Name: Seymour of Sycamore, Inc.
Address: 917 Crosby Ave.
Address:
City: Sycamore State: IL Zip: 60178
For information, call: (800) 435-4482
Emergency Number: 815-895-9101
Emergency Agency:
Number:
MSDS Creation Date: 1/1/2000
Supersedes Date:
Miscellaneous:
PRODUCT/TRADE NAME(S): 20-1413, 24805, 24805-1

CAS #: N/A

CHEMICAL NAME: N/A

BRIEF DESCRIPTION: N/A

**** SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS ****

| Chemical Name | CAS | MIN | MAX |
|-------------------------|-----------|-----|-----|
| ACETONE | 67-64-1 | 20 | 20 |
| ETHYL BENZENE | 100-41-4 | 5 | 5 |
| GLYCOL ETHER EP | 2807-30-9 | 5 | 5 |
| METHYL ISO-BUTYL KETONE | 108-10-1 | 5 | 5 |
| METHYL PROPYL KETONE | 107-87-9 | 5 | 5 |
| N-BUTANE | 106-97-8 | 10 | 10 |
| PROPANE | 74-98-6 | 20 | 20 |

| | | | |
|------------------|------------|----|----|
| SC 100 SOLVENT | 64742-95-6 | 5 | 5 |
| TITANIUM DIOXIDE | 13463-67-7 | 15 | 15 |
| XYLENE | 1330-20-7 | 10 | 10 |
| METHANOL | 67-56-1 | .1 | .1 |

Miscellaneous:

EXPOSURE LIMITS:

| | ACGIH | | OSHA | | COMPANY | |
|--------------------------------|----------|----------|----------|-------------|---------|------|
| | TLV-TWA | TLV-STEL | PEL-TWA | PEL-CEILING | TLV-TWA | SKIN |
| ACETONE | 750 PPM | 1000 PPM | 750 PPM | 1000 PPM | N.E. | YES |
| PROPANE | 1000 PPM | N.E. | 1000 PPM | N.E. | N.E. | NO |
| METHYL- ISO-BUTYL KETONE | 50 PPM | 75 PPM | 50 PPM | 75 PPM | N.E. | YES |
| N-BUTANE | 800 PPM | N.E. | 800 PPM | N.E. | N.E. | NO |
| GLYCOL ETHER EP | 25 PPM | N.E. | 25 PPM | N.E. | N.E. | YES |
| XYLENE | 100 PPM | 150 PPM | 100 PPM | 150 PPM | N.E. | YES |
| SC100 SOLVENT | 50 PPM | N.E. | 50 PPM | N.E. | N.E. | YES |
| METHYL PROPYL KETONE | N.E. | N.E. | N.E. | N.E. | N.E. | NO |
| TITANIUM DIOXIDE | 5MG/M3 | N.E. | 5 MG/M3 | N.E. | N.E. | NO |
| ETHYL BENZENE | 100PPM | 125PPM | 100 PPM | 125 PPM | N.E. | NO |

Lbs of VOC per Gallon Coating (minus water): 0
 Coating Density (lbs/gal): 0
 Solvent Density (lbs/gal): 0
 Percent Solvent (volume): 0
 Percent Solids (volume): 0
 Percent Water (volume): 0

**** SECTION 3 - HAZARDS IDENTIFICATION ****

NFPA: Health: Fire: Reactivity: Other:
 HMIS: Health: 1 Fire: 4 Reactivity: 3 Special Protection:

Miscellaneous:

EMERGENCY OVERVIEW: MAY CAUSE FLASH FIRE OR EXPLOSION.

POTENTIAL HEALTH EFFECTS

Target Organs:

Eye:

A PRIMARY ROUTE OF ENTRY. LIQUID, AEROSOLS AND VAPORS OF THIS PRODUCT ARE IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING ACCOMPANIED BY A STINGING SENSATION AND/OR A FEELING LIKE THAT OF FINE DUST IN THE EYES.

Skin:

A PRIMARY ROUTE OF ENTRY. CAUSES SKIN IRRITATION. ALLERGIC REACTIONS ARE POSSIBLE. MAY CAUSE SKIN SENSITIZATION, AN ALLERGIC REACTION, WHICH BECOMES EVIDENT ON RE-TO THIS MATERIAL. PROLONGED OR REPEATED CONTACT CAN RESULT IN DEFATTING AND DRYING OF THE

SKIN WHICH
MAY RESULT IN SKIN IRRITATION AND DERMATITIS (RASH).

Ingestion:

A PRIMARY ROUTE OF ENTRY. THIS MATERIAL MAY BE HARMFUL OR FATAL IF SWALLOWED.
IRRITATING TO
MOUTH, THROAT AND STOMACH.

Inhalation:

A PRIMARY ROUTE OF ENTRY. HEADACHES, DIZZINESS, NAUSEA, DECREASED BLOOD
CHANGES IN
HEART RATE AND CYANOSIS MAY RESULT FROM OVER-EXPOSURE TO VAPOR OR SKIN EXPOSURE.
PROLONGED
INHALATION MAY BE HARMFUL. CHRONIC HAZARDS: POSSIBLE REPRODUCTIVE HAZARD.

Miscellaneous:

**** SECTION 4 - FIRST AID MEASURES ****

Eye:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. GET MEDICAL ATTENTION, IF IRRITATION
PERSISTS.

Skin:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR
PERSISTS. REMOVE
CONTAMINATED CLOTHING. WASH SKIN WITH SOAP AND WATER. GET MEDICAL ATTENTION.

Ingestion:

IF SWALLOWED, DO NOT INDUCE VOMITING. GIVE VICTIM A GLASS OF WATER OR MILK. CALL
PHYSICIAN
OR POISON CONTROL CENTER IMMEDIATELY. NEVER GIVE ANYTHING BY MOUTH TO AN
UNCONSCIOUS PERSON.

Inhalation:

REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION. IF BREATHING
IS
DIFFICULT, GIVE OXYGEN. GET IMMEDIATE MEDICAL ATTENTION. RESCUERS SHOULD PUT ON
APPROPRIATE
PROTECTIVE GEAR. REMOVE FROM AREA OF EXPOSURE. IF NOT BREATHING, GIVE ARTIFICIAL
RESPIRATION.
IF BREATHING IS DIFFICULT, GIVE OXYGEN. KEEP VICTIM WARM. GET IMMEDIATE MEDICAL
ATTENTION.

Notes to Physician:

**** SECTION 5 - FIRE FIGHTING MEASURES ****

Unusual Fire and Explosion Hazards:

VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR.

Special Fire Fighting Procedures:

CONTAINERS CAN BUILD UP PRESSURE IF EXPOSED TO HEAT (FIRE). AS IN ANY
FIRE, WEAR SELF-CONTAINED BREATHING APPARATUS PRESSURE-DEMAND (MSHA/NIOSH

APPROVED OR EQUIVALENT) AND FULL PROTECTIVE GEAR.

Extinguishing Media:

WATER FOG, DRY CHEMICAL, CO2, ALCOHOL FOAM, FOAM.

Flash Point:

-4 F

Flammable Limits:

Lower Limit:

(LEL): 1.0%

Upper Limit:

(UEL): 12.8%

AutoIgnition Temperature:

General Information:

FLAMMABLE LIMITS: NO DATA

**** SECTION 6 - ACCIDENTAL RELEASE MEASURES ****

Disposal:

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT PUNCTURE, INCINERATE OR COMPACT.

Spills/Leaks:

ABSORB SPILL WITH INERT MATERIAL (E.G. DRY SAND OR EARTH), THEN PLACE IN A WASTE CONTAINER.

**** SECTION 7 - HANDLING and STORAGE ****

Handling:

HANDLING: WASH THOROUGHLY AFTER HANDLING.

Storage:

STORAGE: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

**** SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION ****

Engineering Controls:

LOCAL EXHAUST: LOCAL EXHAUST VENTILATION MAY BE NECESSARY TO CONTROL ANY AIR CONTAMINANTS TO

WITHIN THEIR TLV'S DURING THE USE OF THIS PRODUCT.

MECHANICAL (GENERAL): NO CORRESPONDING DATA IN MSDS PROVIDED BY MANUFACTURER

SPECIAL VENTILATION: NO CORRESPONDING DATA IN MSDS PROVIDED BY MANUFACTURER

OTHER VENTILATION: NO CORRESPONDING DATA IN MSDS PROVIDED BY MANUFACTURER

Eyes:

WEAR SAFETY GLASSES WITH SIDE SHIELDS (OR GOGGLES) AND A FACE SHIELD.

Skin:

PROTECTIVE GLOVES: WHERE CONTACT IS LIKELY, WEAR CHEMICAL RESISTANT GLOVES.

Clothing:

AND OTHER PROTECTIVE EQUIPMENT: WHERE CONTACT IS LIKELY, WEAR CHEMICAL RESISTANT GLOVES, A CHEMICAL SUIT, RUBBER BOOTS, AND CHEMICAL SAFETY GOGGLES PLUS A FACE SHIELD.

Respirators:

A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS. PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

**** SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ****

Appearance/Odor:

AROMATIC ODOR WITH LIQUID APPEARANCE.

pH: NA

Vapor Pressure: (MM HG.): 40 PSI

Vapor Density: (AIR = 1): IS HEAVIER THAN AIR

Evaporation Rate: IS FASTER THAN ETHER

Viscosity:

Boiling Point: -44 TO 344 F

Freezing/Melting Point:

Decomposition Temperature:

Solubility: IN WATER: SLIGHT

Specific Gravity: .8727

Molecular Formula: N/A

Molecular Weight:

Miscellaneous:

% VOLATILE / VOLUME: 48%

**** SECTION 10 - STABILITY AND REACTIVITY ****

Chemical Stability:

STABLE: YES

Conditions to Avoid:

DO NOT STORE ABOVE 120 DEGREES F. KEEP AWAY FROM SPARKS, PILOT LIGHTS, AND OPEN FLAMES.

Incompatibilities with Other Materials:

NO INFORMATION.

Hazardous Decomposition Products:

OR BYPRODUCTS: MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION. FUMES

CONTAIN
CARBON DIOXIDE AND/OR CARBON MONOXIDE.

Hazardous Polymerization:
MAY OCCUR: NO

**** SECTION 11 - TOXICOLOGICAL INFORMATION ****

Toxicological Information:

**** SECTION 12 - ECOLOGICAL INFORMATION ****

Ecological Information:
ECOLOGICAL INFORMATION: THIS PRODUCT DOES NOT CONTAIN CHLORINATED SOLVENTS OR

**** SECTION 13 - OTHER PRECAUTIONS ****

Other Precautions:
NO CORRESPONDING DATA IN MSDS PROVIDED BY MANUFACTURER.

Work/Hygienic Practices:
NO INFORMATION.

**** SECTION 14 - TRANSPORT INFORMATION ****

Transportation Information:
CATEGORY: ORM-D

TRANSFORMATION INFORMATION:
DOT PROPER SHIPPING NAME: CONSUMER COMMODITY ORM-D

Label Information:

**** SECTION 15 - REGULATORY INFORMATION ****

Regulatory Information:
REGULATORY INFORMATION
U.S. FEDERAL REGULATIONS: AS FOLLOWS -
OSHA: HAZARDOUS BY DEFINITION OF HAZARD COMMUNICATION STANDARD (29 CFR 1910.1200).

CERCLA - SARA HAZARD CATEGORY:
THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA 'HAZARD CATEGORIES'
UNDER
SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986
(SARA TITLE
1111) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING

CATEGORIES:
IMMEDIATE HEALTH HAZARD
CHRONIC HEALTH HAZARD
FIRE HAZARD
PRESSURIZED GAS HAZARD

SARA SECTION 313:
THIS PRODUCT CONTAINS THE FOLLOWING SUBSTANCES SUBJECT TO THE REPORTING
REQUIREMENTS OF
SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF
1986 AND 40
CFR PART 372:
GLYCOL ETHER EP
METHYL ISO-BUTYL KETONE
XYLENE
ETHYL BENZENE
METHANOL (CAS# 67-56-1, LESS THAN 0.1%)

INTERNATIONAL REGULATIONS: AS FOLLOWS -
CANADIAN WHMIS: THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT
REGULATIONS
EXCEPT FOR USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS: NO INFORMATION AVAILABLE.

**** SECTION 16 - ADDITIONAL INFORMATION ****

Additional Information:
IDENTIFICATION NUMBER: PART #24805

THIS INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE.
HOWEVER, IT
IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS
AND REGULATIONS.